

## PRODUCT-DETAILS

# OTR25T3M

## OTR25T3M Safety switch



### Información General

|                       |                                                                                                                                                                                                                                                                                                                                                                                            |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | OTR25T3M                                                                                                                                                                                                                                                                                                                                                                                   |
| Product ID            | 1SCA022613R3910                                                                                                                                                                                                                                                                                                                                                                            |
| EAN                   | 6417019199832                                                                                                                                                                                                                                                                                                                                                                              |
| Catalog Description   | OTR25T3M Safety switch                                                                                                                                                                                                                                                                                                                                                                     |
| Long Description      | The enclosure of the OTR series is made of rigid stainless steel, class AISI304. The enclosure has a hinged door, with door lock. The cover is interlocked, and can not be opened when switch is on. The interlock function can be defeated for thermographing. Suitable for outdoor and indoor use. The cable entries are of knock out types. PE terminal and auxiliary contact included. |

### Descargas Populares

|                                   |                   |
|-----------------------------------|-------------------|
| Data Sheet, Technical Information | 1SCC340015C0201   |
| Instructions and Manuals          | 1SCC340006M0013   |
| Mechanical Drawings               | OTLK201510S32.stp |

### Dimensiones

|                    |        |
|--------------------|--------|
| Product Net Width  | 150 mm |
| Product Net Height | 200 mm |

|                            |        |
|----------------------------|--------|
| Product Net Depth / Length | 100 mm |
| Product Net Weight         | 1.9 kg |

## Technical

|                                                     |                                                                                                  |
|-----------------------------------------------------|--------------------------------------------------------------------------------------------------|
| Rated Operational Current<br>AC-22A ( $I_e$ )       | (380 ... 415 V) 45 A<br>(500 V) 45 A<br>(690 V) 45 A                                             |
| Rated Operational Current<br>AC-23A ( $I_e$ )       | (380 ... 415 V) 30 A<br>(500 V) 30 A<br>(690 V) 20 A                                             |
| Rated Operational Power<br>AC-23A ( $P_e$ )         | (380 ... 415 V) 15 kW<br>(500 V) 15 kW<br>(690 V) 15 kW                                          |
| Conventional Thermal<br>Current ( $I_{the}$ )       | Fully Enclosed 63 A                                                                              |
| Rated Insulation Voltage<br>( $U_i$ )               | acc. to IEC/EN 60664-1 750 V                                                                     |
| Rated Operational Voltage                           | Main Circuit 750 V                                                                               |
| Rated Short-Circuit<br>Making Capacity ( $I_{cm}$ ) | (690 V AC) 1.4 kA                                                                                |
| Rated Short-time<br>Withstand Current ( $I_{cw}$ )  | for 1 s 1 kA                                                                                     |
| Power Loss                                          | at Rated Operating Conditions per Pole 2.8 W                                                     |
| Pollution Degree                                    | 3                                                                                                |
| Handle Color                                        | Black                                                                                            |
| Handle Type                                         | Selector handle                                                                                  |
| Position of Line Terminals                          | Top In - Bottom Out                                                                              |
| Standards                                           | IEC 60947-1, -3                                                                                  |
| Number of Poles                                     | 3                                                                                                |
| Connecting Capacity Main<br>Circuit                 | Screw Clamp 1.5...35 mm <sup>2</sup><br>Screw Clamp / PE Terminal 2pcs, 1.5...25 mm <sup>2</sup> |
| Cable Entry Position                                | Up/Down                                                                                          |
| Cable Outlets Per Side                              | 2xø32.5+ø16.5 / 2xø32.5+ø16.5                                                                    |
| Degree of Protection                                | acc. to IEC 60529 IP65                                                                           |
| Enclosure Material                                  | Stainless steel                                                                                  |
| Maximum Mounted<br>Auxiliary Contacts               | 2 NO, 1 NC                                                                                       |
| Mounted Auxiliary<br>Contacts                       | 1 NO, 0 NC                                                                                       |
| Number of Auxiliary<br>Contacts NC                  | 1                                                                                                |
| Position of PE Terminals                            | Top In - Bottom Out                                                                              |

## Ambiente

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificados y Declaraciones (Número de Documento)

|                                   |                 |
|-----------------------------------|-----------------|
| Declaration of Conformity<br>- CE | 1SCC340006D2704 |
| Instructions and Manuals          | 1SCC340006M0013 |
| RoHS Information                  | 1SCC340034D0203 |

Información de Embalaje

|                                   |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | 1 piece       |
| Package Level 1 Width             | 162 mm        |
| Package Level 1 Depth /<br>Length | 222 mm        |
| Package Level 1 Height            | 148 mm        |
| Package Level 1 Gross<br>Weight   | 2 kg          |
| Package Level 1 EAN               | 6417019199832 |

Clasificaciones

|                            |                                                            |
|----------------------------|------------------------------------------------------------|
| Object Classification Code | Q                                                          |
| ETIM 5                     | EC000216 - Switch disconnecter                             |
| ETIM 6                     | EC000216 - Switch disconnecter                             |
| ETIM 7                     | EC000216 - Switch disconnecter                             |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |
| E-Number (Finland)         | 3640425                                                    |

Categorías

Productos y sistemas de baja tensión → Interruptores-seccionadores de seguridad → Interruptores de seguridad en caja → Enclosed Safety Switches

