


PRODUCT-DETAILS

OS400D04FP

OS400D04FP SWITCH FUSE



Información General

Extended Product Type	OS400D04FP
Product ID	1SCA022753R7110
EAN	6417019245300
Catalog Description	OS400D04FP SWITCH FUSE
Long Description	Switch Fuses,Front Operated,4-pole,04 (Left Side),DIN,0,1,2,Handle and shaft included,Switched - Fusible Pole

Descargas Populares

Data Sheet, Technical Information	1SCC311100D0201
Instructions and Manuals	1SCC311015M0215

Dimensiones

Product Net Width	319 mm
Product Net Height	230 mm
Product Net Depth / Length	193 mm
Product Net Weight	8.41 kg 18.54 lb

Technical

Rated Operational Current AC-21A (I_e)	(500 V) 400 A (690 V) 400 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 132 kW (400 V) 220 kW (415 V) 230 kW (500 V) 280 kW (690 V) 400 kW
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 400 A
Conventional Thermal Current (I_{the})	Fully Enclosed 400 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	500 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 14 kiloampere rms
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 45 W
Pollution Degree	3
Handle Type	Handle and shaft included
Fourth Pole Type	Switched - Fusible Pole
Switches Operating Mechanism	04 (Left Side)
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Fuse Size	0,1,2
Fuse System	DIN
Operating Mode	Front Operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	4
Terminal Type	Lug terminals
Terminal Width	25 mm
Tightening Torque	30 ... 44 N·m

Certificados y Declaraciones (Número de Documento)

CCC Certificate	CCC OS315-400 2016
Declaration of Conformity - CE	1SCC311099D2704
DNV GL Certificate	1SCC311131D0202
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_.pdf
Instructions and Manuals	1SCC311015M0215
RoHS Information	1SCC311108D0203

Información de Embalaje		
Package Level 1 Units		1 piece
Package Level 1 Width	240 mm	9.45 in
Package Level 1 Depth / Length	335 mm	13.19 in
Package Level 1 Height	206 mm	8.11 in
Package Level 1 Gross Weight	8.81 kg	19.42 lb
Package Level 1 EAN		6417019245300

Clasificaciones		
Object Classification Code		Q
ETIM 4	EC001040 - Fuse switch disconnecter	
ETIM 5	EC001040 - Fuse switch disconnecter	
ETIM 6	EC001040 - Fuse switch disconnecter	
ETIM 7	EC001040 - Fuse switch disconnecter	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	

Categorías		
Productos y sistemas de baja tensión → Interruptores-seccionadores → Interruptor portafusibles		

