

PRODUCT-DETAILS

A12-30-22 110-115V 50Hz / 115-127V 60Hz

A12-30-22 110-115V 50Hz / 115-127V 60Hz

Contactor



Información General

Extended Product Type	A12-30-22 110-115V 50Hz / 115-127V 60Hz
Product ID	1SBL161001R8922
EAN	3471522043894
Catalog Description	A12-30-22 110-115V 50Hz / 115-127V 60Hz Contactor
Long Description	A12 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The A... series 2-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 1st stack with 3 main poles, 2nd stack with 4 built-in auxiliary contacts, side-mounted add-on auxiliary contact blocks (The built-in auxiliary contact elements are mechanically linked) - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

Clasificaciones

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
UNSPSC	39121529

Información de Embalaje

Package Level 1 Units	1 piece
Package Level 1 Width	78 mm
Package Level 1 Depth / Length	110 mm
Package Level 1 Height	46 mm
Package Level 1 Gross Weight	0.4 kg
Package Level 1 EAN	3471522043894
Package Level 2 Units	box 48 piece
Package Level 2 Width	300 mm
Package Level 2 Depth / Length	245 mm
Package Level 2 Height	308 mm
Package Level 2 Gross Weight	19.2 kg
Package Level 3 Units	576 piece

Certificados y Declaraciones (Número de Documento)

BV Certificate	BV_2634H07559E0
CB Certificate	CB_CN44759
CCC Certificate	CCC_2018010304059156
CSA Certificate	CSA_1041746
Declaration of Conformity - CE	1SBD250801U1000
DNV Certificate	DNV-GL_TAE00000TX
DNV GL Certificate	DNV-GL_TAE00000TX
EAC Certificate	EAC_RU C-FR ME77 B01010
Environmental Information	1SBD250002E1004
GOST Certificate	GOST_POCCFRME77B07175
Instructions and Manuals	FPTC407721P0001
LR Certificate	LRS_9830011E4
RINA Certificate	RINA_ELE128713XG001
RMRS Certificate	RMRS_0507015250
RoHS Information	1SBD250801U1000
UL Certificate	UL_20160205-E312527-10-2
UL Listing Card	UL_E312527

Ambiente

Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... +55 °C Close to Contactor Fitted with Thermal O/L Relay -25 ... +55 °C Close to Contactor without Thermal O/L Relay (Uc) -40 ... +70 °C
Climatic Withstand	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible	3000 m
RoHS Status	Following EU Directive 2011/65/EU

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	2

Number of Auxiliary Contacts NC	2
Standards	Devices complying with international standards IEC 947-1 / 947-4-1, and European standards EN 60 947-1 / 60 947-4-1. Electromagnetic compatibility (EMC) acc. to amendment A11 to IEC 947-1, EN 60 947-1 and amendment 2 to IEC 947-4-1
Rated Operational Voltage	Main Circuit 690 V
Rated Frequency (f)	Supply Circuit 50 60 Hz
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-5-1, q = 40 °C 16 A acc. to IEC 60947-4-1, Open Contactors q = 40 °C 28 A
Rated Operational Current AC-1 (I_e)	(690 V) 40 °C 27 A (690 V) 55 °C 25 A (690 V) 70 °C 20 A
Rated Operational Current AC-3 (I_e)	(220 / 230 / 240 V) 55 °C 12 A (380 / 400 V) 55 °C 12 A (415 V) 55 °C 12 A (440 V) 55 °C 12 A (500 V) 55 °C 12 A (690 V) 55 °C 9 A
Rated Operational Power AC-3 (P_e)	(220 / 230 / 240 V) 3 kW (380 / 400 V) 5.5 kW (415 V) 5.5 kW (440 V) 5.5 kW (500 V) 7.5 kW (690 V) 7.5 kW
Rated Operational Power AC-6b (P_e)	(230 / 240 V) 40 °C, 50 / 60 Hz 7 KVR (230 / 240 V) 55 °C, 50 / 60 Hz 7 KVR (230 / 240 V) 70 °C, 50 / 60 Hz 6 KVR (400 / 415 V) 40 °C, 50 / 60 Hz 11 KVR (400 / 415 V) 70 °C, 50 / 60 Hz 9.5 KVR (400 / 415 V) 55 °C, 50 / 60 Hz 11 KVR (440 V) 40 °C, 50 / 60 Hz 12 KVR (440 V) 55 °C, 50 / 60 Hz 12 KVR (440 V) 70 °C, 50 / 60 Hz 10.5 KVR (500 / 550 V), 40 °C, 50 / 60 Hz 14 KVR (500 / 550 V) 55 °C, 50 / 60 Hz 14 KVR (500 / 550 V) 70 °C, 50 / 60 Hz 12 KVR (690 V) 40 °C, 50 / 60 Hz 19 KVR (690 V) 55 °C, 50 / 60 Hz 19 KVR (690 V) 70 °C, 50 / 60 Hz 16.5 KVR
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x I_e AC-3
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x I_e AC-3
Rated Operational Current AC-15 (I_e)	(220 / 240 V) 4 A (24 / 127 V) 6 A (380 / 440 V) 3 A (500 V) 2 A (690 V) 2 A
Short-Circuit Protective Devices	Auxiliary Circuit - gG Type Fuses 10 A gG Type Fuses 32 A
Maximum Breaking Capacity	$\cos \phi=0.45$ ($\cos \phi=0.35$ for $I_e > 100$ A) at 440 V 250 A $\cos \phi=0.45$ ($\cos \phi=0.35$ for $I_e > 100$ A) at 690 V 90 A
Maximum Electrical Switching Frequency	AC-1 600 cycles per hour AC-2 / AC-4 300 cycles per hour AC-3 1200 cycles per hour
Rated Operational Current DC-13 (I_e)	(125 V) 0.55 / 69 A (24 V) 6 / 144 A (250 V) 0.3 / 75 A (48 V) 2.8 / 134 A (72 V) 1 / 72 A
Rated Insulation Voltage (U_i)	acc. to UL/CSA 600 V acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
Rated Impulse Withstand Voltage (U_{imp})	8 kV

Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U _c)	50 Hz 110 ... 115 V 60 Hz 115 ... 127 V
Coil Consumption	Average Holding Value 50 / 60 Hz 8.2 V·A Average Pull-in Value 50 Hz 74 V·A Average Pull-in Value 60 Hz 70 V·A
Operate Time	Between Coil De-energization and NC Contact Closing 9 ... 16 ms Between Coil De-energization and NO Contact Opening 4 ... 11 ms Between Coil Energization and NC Contact Opening 7 ... 21 ms Between Coil Energization and NO Contact Closing 10 ... 26 ms
Connecting Capacity Main Circuit	Flexible with Cable End 0.75 ... 2.5 mm ² Rigid Cable 1 ... 4 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Cable End 0.75 ... 2.5 mm ² Rigid Cable 1 ... 4 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20
Connecting Terminals (delivered in open position) Main Poles	M 3.5 (+,-) pozidriv 2 screws with cable clamp
Terminal Type	Screw Terminals

Dimensiones

Product Net Width	44 mm
Product Net Depth / Length	107 mm
Product Net Height	74 mm
Product Net Weight	0.4 kg

Descargas Populares

Data Sheet, Technical Information	1SBC100122C0202_Ch02
Instructions and Manuals	FPTC407721P0001

Clasificación

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Contactores → Contactores

