

## PRODUCT-DETAILS

# AF38-30-00-11

## AF38-30-00-11 24-60V50/60HZ 20-60VDC Contactor



### Información General

|                       |                                                |
|-----------------------|------------------------------------------------|
| Extended Product Type | AF38-30-00-11                                  |
| Product ID            | 1SBL297001R1100                                |
| EAN                   | 3471523111516                                  |
| Catalog Description   | AF38-30-00-11 24-60V50/60HZ 20-60VDC Contactor |

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Long Description | <p>AF38 contactors are used for controlling power circuits up to 690 V AC and 220 V DC. They are mainly used for controlling 3-phase motors, non-inductive or slightly inductive loads. AF... contactors include an electronic coil interface accepting a wide control voltage <math>U_c \text{ min.} \dots U_c \text{ max.}</math> Only four coils cover control voltages between 24...500 V 50/60 Hz or 20...500 V DC. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change. AF contactors have built-in surge protection and do not require additional surge suppressors. The AF... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, front and side-mounted add-on auxiliary contact blocks (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1. N.C. mirror contacts compliant with Annex F of IEC 60947-4-1) - Control circuit: AC or DC operated - Accessories: a wide range of accessories is available. Note: AF...-30-...-11 not suitable for a direct control by PLC-output. AF...-30-...-11 contactor type available in some countries: please consult your ABB representative.</p> |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Clasificaciones

|                            |                                           |
|----------------------------|-------------------------------------------|
| Object Classification Code | Q                                         |
| ETIM 4                     | EC000066 - Magnet contactor, AC-switching |
| ETIM 5                     | EC000066 - Magnet contactor, AC-switching |
| ETIM 6                     | EC000066 - Power contactor, AC switching  |

ETIM 7

EC000066 - Power contactor, AC switching

E-Number (Sweden)

3211346

## Información de Embalaje

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 87 mm         |
| Package Level 1 Depth / Length | 87 mm         |
| Package Level 1 Height         | 47 mm         |
| Package Level 1 Gross Weight   | 0.31 kg       |
| Package Level 1 EAN            | 3471523111516 |
| Package Level 2 Units          | box 21 piece  |
| Package Level 2 Width          | 250 mm        |
| Package Level 2 Depth / Length | 300 mm        |
| Package Level 2 Height         | 315 mm        |
| Package Level 2 Gross Weight   | 13.95 kg      |
| Package Level 3 Units          | 1080 piece    |

## Certificados y Declaraciones (Número de Documento)

|                                |                               |
|--------------------------------|-------------------------------|
| ABS Certificate                | ABS_15-GE1349500-PDA_90682247 |
| BV Certificate                 | BV_2634H24898B0               |
| CB Certificate                 | CB_SE-80872M3                 |
| CCC Certificate                | CCC_2010010304445623          |
| cUL Certificate                | UL_20180227_E312527_7_1       |
| Declaration of Conformity - CE | 1SBD250000U1000               |
| DNV Certificate                | DNV-GL_TAE00001AF-3           |
| DNV GL Certificate             | DNV-GL_TAE00001AF-3           |
| EAC Certificate                | EAC_RU C-FR ME77 B03597       |
| Environmental Information      | 1SBD250149E1000               |
| GL Certificate                 | DNV-GL_TAE00001AF-3           |
| GOST Certificate               | GOST_POCCFR.ME77.B07175.pdf   |
| Instructions and Manuals       | 1SBC101027M6801               |
| KC Certificate                 | KC_HW02016-15001A             |
| LR Certificate                 | LRS_1300087E1                 |
| RINA Certificate               | RINA_ELE240318XG              |
| RMRS Certificate               | RMRS_1802705280               |
| RoHS Information               | 1SBD250000U1000               |
| UL Certificate                 | UL_20140305-E312527_7_1       |
| UL Listing Card                | E312527                       |

## Technical UL/CSA

|                              |                                                                                                                                                                                                                              |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General Use Rating<br>UL/CSA | (600 V AC) 50 A                                                                                                                                                                                                              |
| Horsepower Rating<br>UL/CSA  | (220 ... 240 V AC) Three Phase 10 hp<br>(440 ... 480 V AC) Three Phase 25 hp<br>(550 ... 600 V AC) Three Phase 30 hp<br>(120 V AC) Single Phase 2 hp<br>(200 ... 208 V AC) Three Phase 10 hp<br>(240 V AC) Single Phase 5 hp |
| Tightening Torque            | Control Circuit 11 lA                                                                                                                                                                                                        |

UL/CSA

Main Circuit 22 IA

## Ambiente

|                                                |                                                                                                                                                                                              |
|------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ambient Air Temperature                        | Close to Contactor for Storage -60 ... +80 °C<br>Close to Contactor without Thermal O/L Relay -40 ... +70 °C<br>Close to Contactor Fitted with Thermal O/L Relay -25 ... +60 °C              |
| Climatic Withstand                             | Category B according to IEC 60947-1 Annex Q                                                                                                                                                  |
| Maximum Operating Altitude Permissible         | 3000 m                                                                                                                                                                                       |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5 ... 300 Hz 4 g closed position / 2 g open position                                                                                                                                         |
| Resistance to Shock acc. to IEC 60068-2-27     | Shock Direction: A 30 K40<br>Shock Direction: B2 15 K40<br>Shock Direction: C1 25 K40<br>Shock Direction: C2 25 K40<br>Closed, Shock Direction: B1 25 K40<br>Open, Shock Direction: B1 5 K40 |
| RoHS Status                                    | Following EU Directive 2011/65/EU                                                                                                                                                            |

## Technical

|                                                    |                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of Main Contacts NO                         | 3                                                                                                                                                                                                                                                                                                                                                                      |
| Number of Main Contacts NC                         | 0                                                                                                                                                                                                                                                                                                                                                                      |
| Number of Auxiliary Contacts NO                    | 0                                                                                                                                                                                                                                                                                                                                                                      |
| Number of Auxiliary Contacts NC                    | 0                                                                                                                                                                                                                                                                                                                                                                      |
| Standards                                          | IEC 60947-1 / 60947-4-1 and EN 60947-1 / 60947-4-1, UL 508, CSA C22.2 N° 14                                                                                                                                                                                                                                                                                            |
| Rated Operational Voltage                          | Main Circuit 690 V                                                                                                                                                                                                                                                                                                                                                     |
| Rated Frequency (f)                                | Main Circuit 50 / 60 Hz                                                                                                                                                                                                                                                                                                                                                |
| Conventional Free-air Thermal Current ( $I_{th}$ ) | acc. to IEC 60947-4-1, Open Contactors q = 40 °C 50 A                                                                                                                                                                                                                                                                                                                  |
| Rated Operational Current AC-1 ( $I_e$ )           | (690 V) 40 °C 50 A<br>(690 V) 60 °C 42 A<br>(690 V) 70 °C 37 A                                                                                                                                                                                                                                                                                                         |
| Rated Operational Current AC-3 ( $I_e$ )           | (220 / 230 / 240 V) 60 °C 40 A<br>(380 / 400 V) 60 °C 38 A<br>(415 V) 60 °C 38 A<br>(440 V) 60 °C 38 A<br>(500 V) 60 °C 33 A<br>(690 V) 60 °C 24 A                                                                                                                                                                                                                     |
| Rated Operational Power AC-3 ( $P_e$ )             | (220 / 230 / 240 V) 11 kW<br>(380 / 400 V) 18.5 kW<br>(415 V) 18.5 kW<br>(440 V) 22 kW<br>(500 V) 22 kW<br>(690 V) 22 kW<br>(400 V) 18.5 kW                                                                                                                                                                                                                            |
| Rated Short-time Withstand Current ( $I_{cw}$ )    | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 350 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 50 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 150 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 700 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 225 A<br>for 1 s -empty- A |
| Maximum Breaking Capacity                          | cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 500 A<br>cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 200 A                                                                                                                                                                                                                                           |
| Maximum Electrical Switching Frequency             | AC-1 600 cycles per hour<br>AC-2 / AC-4 150 cycles per hour<br>AC-3 1200 cycles per hour                                                                                                                                                                                                                                                                               |
| Rated Insulation Voltage ( $U_i$ )                 | acc. to UL/CSA 600 V<br>acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V                                                                                                                                                                                                                                                                                               |

|                                                     |                                                                                                                                                                                                                                                                        |
|-----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rated Impulse Withstand Voltage (U <sub>imp</sub> ) | 6 kV                                                                                                                                                                                                                                                                   |
| Maximum Mechanical Switching Frequency              | 3600 cycles per hour                                                                                                                                                                                                                                                   |
| Rated Control Circuit Voltage (U <sub>c</sub> )     | 50 Hz 24 ... 60 V<br>50 Hz / 60 Hz 24 ... 60 V<br>60 Hz 24 ... 60 V<br>DC Operation 20 ... 60 V                                                                                                                                                                        |
| Operate Time                                        | Between Coil De-energization and NC Contact Closing 13 ... 98 ms<br>Between Coil De-energization and NO Contact Opening 11 ... 95 ms<br>Between Coil Energization and NC Contact Opening 38 ... 90 ms<br>Between Coil Energization and NO Contact Closing 40 ... 95 ms |
| Connecting Capacity Main Circuit                    | Rigid 1/2x 2.5 ... 10 m <sup>2</sup><br>Flexible with Ferrule 1/2x 1.5 ... 10 m <sup>2</sup><br>Flexible with Insulated Ferrule 1x 1.5 ... 10 m <sup>2</sup><br>Flexible with Insulated Ferrule 2x 1.5 ... 4 m <sup>2</sup>                                            |
| Connecting Capacity Control Circuit                 | Flexible with Ferrule 1/2x 0.75 ... 2.5 m <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 m <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 m <sup>2</sup><br>Rigid 1/2x 1 ... 2.5 m <sup>2</sup>                                      |
| Wire Stripping Length                               | Control Circuit 10 mm<br>Main Circuit 14 mm                                                                                                                                                                                                                            |
| Degree of Protection                                | acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20                                                                                                                                           |
| Terminal Type                                       | Screw Terminals                                                                                                                                                                                                                                                        |

## Dimensiones

|                            |         |
|----------------------------|---------|
| Product Net Width          | 45 mm   |
| Product Net Depth / Length | 86 mm   |
| Product Net Height         | 86 mm   |
| Product Net Weight         | 0.31 kg |

## Descargas Populares

|                          |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 1SBC101027M6801 |
|--------------------------|-----------------|

## Clasificación

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85364900 |

## Categorías

Productos y sistemas de baja tensión → Aparatos de control → Contactores → Contactores

