

PRODUCT-DETAILS

OTP25A3M

OTP25A3M Safety switch



General Information

Extended Product Type	OTP25A3M
Product ID	1SCA022399R6670
EAN	6417019130231
Catalog Description	OTP25A3M Safety switch

Long Description

The enclosure in the OTP series is using a rigid glass reinforced polycarbonate enclosure. The enclosure is UV protected, protected against low-pressure water jets (IP65), and hence built for outdoor and indoor use. The cable entries are threaded and have knock out holes for 2 parallel cables and one control cable, both from top and bottom. The handle is padlockable and made for three padlocks. The cover is interlocked. The interlocking can be by-passed, for thermographing etc. The switch is made for 5 wire system, and have a fixed neutral terminal and PE terminal.

Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
Instructions and Manuals	1SCC340002M0012
Mechanical Drawings	OTPK201490SM32.stp

Dimensions

Product Net Width	145 mm
-------------------	--------

Product Net Height	200 mm
Product Net Depth / Length	90 mm
Product Net Weight	0.9 kg

Technical

Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 45 A (500 V) 45 A (690 V) 45 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 30 A (500 V) 30 A (690 V) 20 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 15 kW (500 V) 15 kW (690 V) 15 kW
Conventional Thermal Current (I_{the})	Fully Enclosed 63 A
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V AC) 1.4 kA
Rated Short-time Withstand Current (I_{cw})	for 1 s 1 kA
Power Loss	at Rated Operating Conditions per Pole 2.8 W
Pollution Degree	3
Handle Color	Red / Yellow
Handle Type	Selector handle
Standards	IEC 60947-1, -3
Number of Poles	3
Connecting Capacity Main Circuit	Screw Clamp 0.75...10 mm ² Screw Clamp / PE Terminal 2pcs, 1.5...35 mm ²
Cable Entry Position	Up/Down
Cable Outlets Per Side	2xM32+M16 / 2xM32+M16
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Material	Plastic
Maximum Mounted Auxiliary Contacts	2 NO, 2 NC
Mounted Auxiliary Contacts	1 NO, 0 NC

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

BV Certificate	1SCC340018D0204
Declaration of Conformity - CE	1SCC340003D2704

DNV GL Certificate	1SCC340045D0204
Instructions and Manuals	1SCC340002M0012
RoHS Information	1SCC340034D0203

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	162 mm
Package Level 1 Depth / Length	222 mm
Package Level 1 Height	148 mm
Package Level 1 Gross Weight	1 kg
Package Level 1 EAN	6417019130231

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3642264
E-Number (Norway)	1429402

Categories

Low Voltage Products and Systems → Enclosed Switches → Enclosed Safety Switches → Enclosed Safety Switches

