


PRODUCT-DETAILS

OTM160E3WCM24D

OTM160E3WCM24D MOTORIZED C/O SWITCH



Información General

Extended Product Type	OTM160E3WCM24D
Product ID	1SCA022846R3290
EAN	6417019297019
Catalog Description	OTM160E3WCM24D MOTORIZED C/O SWITCH
Long Description	Including a handle for manual operation, bolt kit with nut and washers for all terminals and male connectors for control circuits. Extended phase distance.

Descargas Populares

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303002M0204

Dimensiones

Product Net Width	296 mm
Product Net Height	170 mm
Product Net Depth / Length	197 mm
Product Net Weight	6.9 kg

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Current AC-31B (I_e)	(380 ... 415 V) 160 A
Rated Operational Current AC-33B (I_e)	(380 ... 415 V) 160 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 90 kW (500 V) 110 kW (690 V) 160 kW
Conventional Free-air Thermal Current (I_{th})	$q = 40^\circ\text{C}$ 160 A
Conventional Thermal Current (I_{the})	Fully Enclosed 160 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 8 kiloampere rms
Motor Operational Voltage	24 V DC
Power Loss	2.4 W
Pollution Degree	3
Handle Color	Black
Handle Type	Direct mounted handle
Switches Operating Mechanism	Mechanism at the End of the Switch
Distance Between Phases	Wide phase distance
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP20

Ambiente

Environmental Information	1SCC303036D0202
---------------------------	-----------------

Certificados y Declaraciones (Número de Documento)

Declaration of Conformity - CE	1SCC303031D0201
Environmental Information	1SCC303036D0202
Instructions and Manuals	1SCC303002M0204
RoHS Information	1SCC303036D0202

Información de Embalaje	
Package Level 1 Units	1 piece
Package Level 1 Width	215 mm
Package Level 1 Depth / Length	395 mm
Package Level 1 Height	215 mm
Package Level 1 Gross Weight	5.7 kg
Package Level 1 EAN	6417019297019

Clasificaciones	
Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categorías
Productos y sistemas de baja tensión → Interruptores-seccionadores → Change-over and Transfer Switches → Motorized Change-over Switches

