



Series C, F-frame Molded Case Mining Circuit Breaker

E2F3030

UPC:786679064511

Dimensions:

Height: 6 INLength: 3.38 INWidth: 4.13 IN

Weight: 4.5 LB

Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

Type: Specialty sealedAmperage Rating: 30A

 Interrupt Rating: 65 kAIC at 240V, 25 kAIC at 480V, 18 kAIC at 600V, 10 kAIC at 250 Vdc

Number Of Poles: Three-poleVoltage Rating: 250 Vdc

• Frame Size: F-frame

• Magnetic Trip Range: 90-300A

• Maximum Voltage: 600V

• Series: Series C

• Terminals: Line and load

• Trip Type: Non-interchangeable magnetic

Supporting documents:

• E2 Mining Series Sales Brochure

• Eatons Volume 4-Circuit Protection

Eaton Specification Sheet - E2F3030

Certifications:

- UL Listed
- CSA Certified



P	ro	duc	t co	mnli	iance:	No	Data
	ı	uuc		шрп	iaiice.	INO	Data

© 2016 Eaton. All rights reserved.