



Essential LED Panel

RC091V LED36S/840 PSU W60L60 LA

ESSENTIAL - Power supply unit external - White

The Essential LED Panel is a highly efficient LED panel at a very competitive price.

Product data

General Information			
Lamp family code	ESSENTIAL	Overall width	600 mm
Light source replaceable	No	Overall height	600 mm
Driver/power unit/transformer	Power supply unit external	Overall diameter	600 mm
Driver included	Yes	Color	White
Connection	Connection unit 2-pole	Approval and Application	
Cable	Cable 0.25m without plug	Ingress protection code	IP20 [Finger-protected]
Protection class IEC	Safety class II	Initial Performance (IEC Compliant)	
Constant light output	No	Initial luminous flux (system flux)	3600 lm
Pole type	Pole	Luminous flux tolerance	+/-10%
Operating and Electrical		Initial LED luminaire efficacy	90 lm/W
Input Voltage	120 to 277 V	Init. Corr. Color Temperature	4000 K
Input Frequency	50 or 60 Hz	Init. Color Rendering Index	≥80
Inrush current	3.4 A	Initial input power	40 W
Inrush time	77 ms	Power consumption tolerance	+/-10%
Power Factor (Min)	0.9	Over Time Performance (IEC Compliant)	
Controls and Dimming		Median useful life L70B50	25.000 h
Dimmable	No	Application Conditions	
Mechanical and Housing		Ambient temperature range	+10 to +35 °C
Housing Material	Aluminum		

Essential LED Panel

Product Data	
Full product code	871016332659799
Order product name	RC091V LED36S/840 PSU W60L60 LA
EAN/UPC - Product	8710163326597
Order code	911401724152
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	4
Material Nr. (12NC)	911401724152
Net Weight (Piece)	2.200 kg

