



Essential LED Panel RC035

RC035B LED40S/865 120-277 W60L60 LA

Power supply unit (On/Off), White

The Essential LED Panel is the most cost-effective LED solution, offering qualified and reliable lighting in work areas, with an extended life cycle, creating a brighter and healthier office environment.

Warnings and Safety

- For indoor use only
- The luminaire must not be used or stored in a corrosive environment where hazardous material such as sulfur, chlorine, etc. is present

Product data

General Information	
Light source replaceable	No
Driver included	Yes
Light Technical	
Luminous Flux	4,000 lm
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	100 lm/W
Color rendering index (CRI)	≥80
Operating and Electrical	
Input Voltage	120 to 277 V
Line Frequency	50 to 60 Hz
Inrush current	12.6 A

Inrush time	0.03 ms
Power Consumption	40 W
Power Factor (Fraction)	0.9
Connection	Flying leads/wires
Cable	Cable without plug 3-pole
Temperature	
Ambient temperature range	+10 to +35 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No

Essential LED Panel RC035

Mechanical and Housing	
Housing Material	Steel
Housing Color	White
Overall length	605 mm
Overall width	605 mm
Overall height	33 mm
Dimensions (Height x Width x Depth)	33 x 605 x 605 mm

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)	
Luminous flux tolerance	-10% / +10%
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)	
Median useful life L70B50	30,000 hour(s)

Product Data	
Order product name	RC035B LED40S/865 120-277 W60L60 LA
Full product name	RC035B LED40S/865 120-277 W60L60 LA
Full product code	872016950065599
Order code	911401897584
Material Nr. (12NC)	911401897584
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169500655
Numerator - Packs per outer box	6
EAN/UPC - Case	8719514961791

