



SmartBright LED Panel RC048 G3

RC048B LED42S/840 100-277 W60L60 LA

Power supply unit, White

The SmartBright LED Panel is the most economical LED solution that provides reliable and qualified lighting in work areas within a long lifetime, creating a brighter and healthier office environment.

Warnings and Safety

- For indoor use only
- The luminaire must not be used or stored in a corrosive environment where hazardous materials such as sulfur, chlorine, thalates, etc. are present

Product data

General Information	
Light source replaceable	No
Driver included	Yes
Light Technical	
Luminous Flux	4,260 lm
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	125 lm/W
Color rendering index (CRI)	≥80
Operating and Electrical	
Input Voltage	100 to 277 V
Line Frequency	50 or 60 Hz
Inrush current	10.24 A

Inrush time	0.027 ms
Power Consumption	34 W
Power Factor (Fraction)	0.9
Connection	Connection unit 2-pole
Cable	-
Protection class IEC	Safety class II
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit
Constant light output	No
Mechanical and Housing	
Housing Material	Aluminum

SmartBright LED Panel RC048 G3

Housing Color	White
Overall height	34 mm
Ingress protection code	IP20/40 [Finger-protected;Wire-protected]
Net Weight (Piece)	1.350 kg

Approval and Application

Ambient temperature range	-10 to +35 °C
---------------------------	---------------

Initial Performance (IEC Compliant)

Luminous flux tolerance	-10% / +10%
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Median useful life L70B50	50,000 hour(s)
---------------------------	----------------

Product Data	
Order product name	RC048B LED42S/840 100-277 W60L60 LA
Full product name	RC048B LED42S/840 100-277 W60L60 LA
Full product code	872016951367999
Order code	911401857585
Material Nr. (12NC)	911401857585
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169513679
Numerator - Packs per outer box	6
EAN/UPC - Case	8720169513754

