



Principal

Gama	Acti 9
Tipo de producto o componente	Double OC or fault contact
Device short name	IOF/SD+OF
Signal contacts composition	2 C/O
[In] rated current	1 A at 130 V DC 1.5 A at 60 V DC 2 A at 48 V DC 6 A at 24 V DC 3 A at 415 V AC - 50/60 Hz 6 A at 240 V AC - 50/60 Hz
9 mm pitches	1

Complementos

Compatibilidad de la gama	Acti 9 iC60 Acti 9 iDPN Vigi Acti 9 iID Acti 9 iSW-NA Acti 9 iC60 RCBO Acti 9 iC65 Acti 9 ARA Acti 9 RCA Acti 9 iDPN (China version)
[Ui] rated insulation voltage	4 kV
Señalizaciones en local	Mechanical indicator
Mounting mode	Fixed
Mounting support	DIN rail
Altura	90 mm
Anchura	9 mm
Profundidad	73 mm
Peso del producto	43 g
Colour	White
Conexiones - terminales	Screw clamp terminal 2 cable(s) 2.5 mm ² rigid Screw clamp terminal 1 cable(s) 0.5...2.5 mm ² flexible Screw clamp terminal 1 cable(s) 1...4 mm ² rigid Screw clamp terminal 2 cable(s) 1.5 mm ² flexible with ferrule
Wire stripping length	10 mm
Tightening torque	1 N.m

Ambiente

Normas	EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Temperatura ambiente de trabajo	-35...70 °C
Temperatura ambiente de almacenamiento	-40...85 °C

Oferta sustentable

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Perfil Medioambiental
Product end of life instructions	Available Manual De Gestión Residuos

Garantía contractual

Warranty period	18 months
-----------------	-----------