PHILIPS

BVC080 LED45/MCCT G2 Solar

911401807503



BVC080 MCCT G2 CCT selectable - Solar Flood Light

Solar flood light with lithium ferro phosphate battery built in the luminaire, Remote controller and installation accessories included. IP65, plastic housing. Available in 1600, 2500, 3600, and 4500 Lumens.

Warnings and Safety

- Install the luminaire in a sunny place that is not shaded by trees, buildings and walls, then the solar panel can receive the maximum sunlight for charging the battery.
- Charge the product under sunlight for at least 8 hours before first time using.
- This luminaire does not need any external electrical connection. It works 100% on solar energy.

General Information

Driver included	Yes
Warranty period	2 years

Light Technical

Luminous Flux	4,500 lm
Correlated Color Temperature (Nom)	Selectable
Luminous Efficacy (rated) (Nom)	160 lm/W
Color rendering index (CRI)	>70

Operating and Electrical

Battery type	LiFePO4
Battery ampere hour	5 Ah
Battery voltage	16 V
Battery charging & discharging cycles	1000
Panel type	Mono crystalline
Panel voltage	22 V
Charge controller type	PWM
Charge controller wattage	28 W

Cable connection kit	Included
Cable	5m cable for Solar panel connection included
Grid connection type	Off grid

Controls and Dimming

Dimmable	Preset Dimming
Configurability	Not configurable
Control interface	-
Solar dimming profile	different modes by remote control

Mechanical and Housing

Housing Color	Grey
Overall length	312 mm
Overall width	234 mm
Overall height	50 mm
Dimensions (Height x Width x Depth)	50 x 234 x 312 mm
Material	Polycarbonate
Battery location	inbuilt luminaire housing
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Optical cover type	Polycarbonate bowl/cover
Net Weight (Piece)	3.800 kg

Approval and Application

CE mark	Yes
EU RoHS compliant	Yes
Ambient temperature range	0 to +50 °C

Over Time Performance (IEC Compliant)

Median useful life L70B50	35,000 hour(s)

Product Data

Order product name	BVC080 LED45/MCCT G2 Solar
Full product name	BVC080 LED45/MCCT G2 Solar
Full product code	872110332406199
Order code	911401807503
Material Nr. (12NC)	911401807503
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8721103324061
Numerator - Packs per outer box	4
EAN/UPC - Case	8721103324108

Dimensional drawing

Related Documents

Photometry and lighting design	Document Name	Download
IES File	BVC080-MCCT-G2-4500lm.IES	Download

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.