

PRODUCT-DETAILS

CK1-11

CK1-11 Short Circuit Signaling Contact



Información General

Extended Product Type	CK1-11
Product ID	1SAM301901R1001
EAN	4013614403927
Catalog Description	CK1-11 Short Circuit Signaling Contact
Long Description	CK1-11 Short-Circuit Signal Contact 1 NO + 1 NC

Clasificación

Minimum Order Quantity	2 piece
Customs Tariff Number	85365080

Descargas Populares

Data Sheet, Technical Information	1SBC100192C02--
Instructions and Manuals	2CDC131027M6802

Dimensiones

Product Net Width	9 mm
Product Net Height	90 mm
Product Net Depth /	78 mm

Length

Product Net Weight	0.035 kg
--------------------	----------

Technical

Terminal Type	Screw Terminals
Rated Operational Voltage	690 V AC 600 V DC Main Circuit 690 V
Rated Operational Current AC-15 (I _e)	(240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A
Rated Operational Current DC-13 (I _e)	(125 V) 0.55 A (24 V) 2 A (250 V) 0.27 A (440 V) 0.15 A (600 V) 0.15 A
Rated Impulse Withstand Voltage (U _{imp})	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U _i)	690 V
Degree of Protection	IP20
Electrical Durability	10000 cycle
Mechanical Durability	10000 cycle
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1/2x 0.75 ... 1.5 mm ² Flexible 1/2x 0.75 ... 1.5 mm ² Rigid 1/2x 1 ... 1.5 mm ²
Tightening Torque	Auxiliary Circuit 0.8 ... 1.2 N·m
Wire Stripping Length	Auxiliary Circuit 8 mm
Recommended Screw Driver	M3 Pozidriv 2
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Standards	CSA 22.2 No. 14 IEC/EN 60947-1 IEC/EN 60947-5-1 UL 508 UL 60947-1 UL 60947-5-1
Product Name	Short Circuit Signaling Contact
Suitable For	MS132 MS165
Suitable for Product Class	Manual Motor Starter
Accessory Group	Electrical
Accessory Type	Short Circuit Signaling Contact

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V AC
Connecting Capacity Auxiliary Circuit UL/CSA	Flexible 1/2x 16-14 AWG Stranded 1/2x 16-14 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 7 in·lb
Contact Rating UL/CSA	B600 Q600

Ambiente

Ambient Air Temperature	Funcionamiento -25 ... +60 °C Almacenamiento -50 ... +80 °C
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 25g
Resistance to Vibrations acc. to IEC 60068-2-6	5g / 3 ... 150 Hz
RoHS Status	Following EU Directive 2011/65/EU

Certificados y Declaraciones (Número de Documento)

ABS Certificate	1SAA963001-0101
BV Certificate	1SAA963002-0201
CB Certificate	1SAA963001-2002
CCC Certificate	1SAA963003-3802
cUL Certificate	cUL_E137861
Declaration of Conformity - CE	1SAD938504-0196 1SAD938507-0190 1SAD938504-0198 1SAD938505-0197 1SAD938507-0188 1SAD938514-0125
DNV GL Certificate	1SAA963001-0304
Instructions and Manuals	2CDC131027M6802
LR Certificate	1SAA963001-0502 1SAA918001-0501
RINA Certificate	Rina_MS132
RoHS Information	1SAD938501-0197 1SAD938511-0125 1SAD938501-0196 1SAD938503-0188 1SAD938503-0190 1SAD938501-0198
UL Certificate	UL_E137861

Información de Embalaje

Package Level 1 Width	25 mm
Package Level 1 Depth / Length	80 mm
Package Level 1 Height	93 mm
Package Level 1 Gross Weight	0.08 kg
Package Level 1 EAN	4013614481529
Package Level 1 Units	2 piece
Package Level 2 Width	280 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Height	210 mm
Package Level 2 EAN	4013614526015
Package Level 2 Units	160 piece

Clasificaciones

Object Classification Code	Q
ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC000041 - Auxiliary contact block

ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
eClass	7.0 27371302
UNSPSC	39121522
IDEA Granular Category Code (IGCC)	4742 >> Electrical contacts
E-Number (Sweden)	3110145

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Guardamotores → Manual Motor Starters Accessories

