

PRODUCT-DETAILS

DBL250

DBL250 Screw Clamp Power distribution Terminal Blocks



Información General

Extended Product Type	DBL250
Product ID	1SNL325010R0000
EAN	3472599856554
Catalog Description	DBL250 Screw Clamp Power distribution Terminal Blocks
Long Description	- 12 connections: distribute unipolar and multipolar power lines, or combine several inputs - Mount it on Din rail or plate and save up to 50% rail space compared to conventional copper bars - Reduce the assembly time by 80% by avoiding to use fastening and isolating components - Easy identification with the reversible cover and delivered pre-printed markers L1, L2, L3, N, PE, +, -.

Clasificación

Color	Grey
Minimum Order Quantity	1 piece
Customs Tariff Number	85369010

Descargas Populares

Data Sheet, Technical Information	1SNC166016D0201
Instructions and Manuals	1SNC166001B0201

Dimensiones

Product Net Width	46 mm
Product Net Height	96 mm
Product Net Depth / Length	60 mm
Product Net Weight	439 g

Technical

Rated Cross-Section	95 mm ²
Spacing	46 mm
Connection Type	Screw Clamp
Function	Feed-through
Number of Levels	1
Connecting Capacity Main Circuit	Screw Clamp / Rigid 1x 35 ... 120 mm ²
Rated Current (I_n)	Main Circuit 250 A
Rated Short-time Withstand Current (I_{cw})	for 1 s 11400 A
Rated Impulse Withstand Voltage (U_{imp})	8000 V
Dielectric Test Voltage	2200 V
Pollution Degree	3
Power Loss	8 W
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Insulation Material	Polyamide
Mounting on DIN Rail	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Tightening Torque	Main Circuit 19 ... 21 N·m

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 1000 V
Connecting Capacity UL/CSA	Stranded 250 AWG
Flammability According to UL94	V-0
Short-Circuit Current Rating (SCCR)	100 kA

Ambiente

Ambient Air Temperature	Funcionamiento -55 ... +110 °C Almacenamiento -55 ... +110 °C
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Certificados y Declaraciones (Número de Documento)

BV Certificate	1SND166008A0200
CB Certificate	1SND166005A0201
CSA Certificate	1SND166007A0201
cUL Certificate	1SND166006A0201
Declaration of Conformity - CE	1SND225005U1000
EAC Certificate	1SND161011A1100
Environmental Information	1SND220095E1000
Instructions and Manuals	1SNC166001B0201
RoHS Information	1SND230557F0201

Clasificaciones

Object Classification Code	X
ETIM 4	EC000276 - Distribution terminal block
ETIM 5	EC000276 - Distribution terminal block
ETIM 6	EC000276 - Distribution terminal block

Información de Embalaje

Package Level 1 Units	1 piece
Package Level 1 Width	68 mm
Package Level 1 Depth / Length	115 mm
Package Level 1 Height	57 mm
Package Level 1 Gross Weight	0.46 kg
Package Level 1 EAN	3472599856554
Package Level 2 Units	20 piece
Package Level 2 Width	230 mm
Package Level 2 Depth / Length	380 mm
Package Level 2 Height	310 mm
Package Level 2 Gross Weight	9.2 kg

Categorías

Productos y sistemas de baja tensión → Accesorios de conexión → Bornas de conexión → SNK Series

