

PRODUCT-DETAILS

EH04-11

EH04-11 Auxiliary Contact



Información General

Extended Product Type	EH04-11
Product ID	GHE3401321R0002
EAN	4013614084775
Catalog Description	EH04-11 Auxiliary Contact
Long Description	EH04-11 Aux.-contact 1NO+1NC

Clasificación

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Descargas Populares

Data Sheet, Technical Information	2CDC103023C0201
Instructions and Manuals	2CDC103025M6801

Dimensiones

Product Net Width	9 mm
Product Net Depth / Length	65 mm

Product Net Height	85 mm
Product Net Weight	0.04 kg

Technical

Rated Operational Voltage	Auxiliary Circuit 500 V AC
Rated Frequency (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz
Rated Impulse Withstand Voltage (U _{imp})	Auxiliary Circuit 4 kV
Rated Insulation Voltage (U _i)	500 V
Degree of Protection	IP20
Mechanical Durability	1000000 cycle
Pollution Degree	3
Tightening Torque	Auxiliary Circuit 0.9 N·m
Wire Stripping Length	Auxiliary Circuit, Top Terminals (1x 1.5) 7 mm Auxiliary Circuit, Top Terminals (1x 2.5 ... 4) 17 mm Auxiliary Circuit, Top Terminals (2x 1.5) 17 mm Auxiliary Circuit, Bottom Terminals (1x 1.5) 7 mm Auxiliary Circuit, Bottom Terminals (2x 1.5) 9 mm Auxiliary Circuit, Bottom Terminals (1x 2.5 ... 4) 9 mm
Standards	IEC/EN 60941-5-1 IEC/EN 60947-1 UL 60947-1 UL 60947-4-1
Number of Auxiliary Contacts NO	1
Product Name	Auxiliary Contact
Suitable For	ESB24 ESB40 ESB63 EN24 EN40
Suitable for Product Class	Installation Contactors

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Auxiliary Circuit 600 V AC/DC
Connecting Capacity Auxiliary Circuit UL/CSA	Stranded 18-12 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 8 in·lb

Ambiente

Ambient Air Temperature	Funcionamiento -25 ... +55 °C Almacenamiento -40 ... +80 °C
Conventional Free-air Thermal Current (I _{th})	Auxiliary Circuit 6 A
Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 15g
Resistance to Vibrations acc. to IEC 60068-2-6	5g / 3 ... 150 Hz
RoHS Status	Following EU Directive 2011/65/EU

Certificados y Declaraciones (Número de Documento)

BV Certificate	1SAA920000-0204
CB Certificate	1SAA920003-2001
CCC Certificate	1SAA920001-3802
CEBEC Certificate	1SAA920001-2002
cUL Certificate	cUL E191658
Declaration of Conformity - CE	1SAD938513-0007
EAC Certificate	1SAA938002-2701
GL Certificate	1SAA920000-0403
Instructions and Manuals	2CDC103025M6801
RMRS Certificate	1SAA920000-0704
RoHS Information	1SAD938512-0007

Información de Embalaje

Package Level 1 Width	93 mm
Package Level 1 Depth / Length	93 mm
Package Level 1 Height	78 mm
Package Level 1 Gross Weight	0.44 kg
Package Level 1 EAN	4013614420924
Package Level 1 Units	10 piece

Clasificaciones

Object Classification Code	K
ETIM 4	EC000041 - Auxiliary contact block
ETIM 5	EC000041 - Auxiliary contact block
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
eClass	7.0 27371302
UNSPSC	39121522

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Contactores → Installation Contactors Accessories

Productos y sistemas de baja tensión → Aparatos modulares de instalación → Aparatos modulares de instalación → Installation Contactors Accessories

