



Principal

Gama	ClimaSys
Product name	ClimaSys CV
Tipo de producto o componente	Fan
Type of ventilation filter	Standard
Air flow	Free flow rate with standard filter: 85 m3/h at 50 Hz Free flow rate with standard filter: 98 m3/h at 60 Hz
[Us] rated supply voltage	175...253 V
Input voltage	230 V 50/60 Hz

Complementos

Rango de potencia	15 W 60 Hz 17 W 50 Hz
[In] rated current	0.121 A 50 Hz 0.097 A 60 Hz
Noise level	46...49 dB
Bearing type	Ball
Height	External: 170 mm
Width	External: 150 mm
Depth	External: 62 mm
Cut-out dimensions	125 x 125 mm
Peso del producto	0.78 kg
Material	Injected thermoplastic (ASA PC)for outlet grille
Colour	Outlet grille: grey RAL 7035
Temperatura ambiente de trabajo	-20...60 °C
Temperatura ambiente de almacenamiento	-40...70 °C
Maximum pressure	50 Pa flow rate 0 m³/h
Conexiones - terminales	Faston connector
IP degree of protection	IP54
Device composition	1 outlet grille front 1 axial motor 2 protective grille on the front and rear surfaces 1 filter front of axial motor 1 cut-out template 1 power cord
Estado de uso	Outside temperature must be 5 °C lower than inside temperature Filter must be cleaned and replaced regularly Surrounding environment must be relatively clean Overfrequent filter replacement should be avoided Flow rates depends on the work point, see ProClima software

Oferta sustentable

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

Garantía contractual

Warranty period	18 months
-----------------	-----------