



### Principal

Gama	ClimaSys
Product name	ClimaSys CC
Tipo de producto o componente	Simple thermostat
Temperature setting range	0...60 °C
Information displayed	Temperature in °C

### Complementos

Input voltage	250 V
Sensor type	Bimetal
Contacts type and composition	NO
Contact resistance	< 10 mOhm
Service life in cycles	>= 100000 Ciclos
Maximum switching capacity	10 A 250 V AC resistivo 15 A 120 V AC resistivo 30 W CC 2 A 120...250 V AC inductivo pf: 0.6
Electrical connection	4 terminals 2.5 mm <sup>2</sup>
Mounting mode	Clipped
Height	External: 68 mm
Width	External: 33 mm
Depth	External: 44 mm
Peso del producto	40 g
Mounting location	35 mm DIN rail Cross rails Spacial upright On mounting plate
Temperatura ambiente de trabajo	-20...80 °C
Grado IP	IP20
Hysteresis	7 %
Number of outputs	1 output(s) ventilation function
Material	PC
Colour	Light grey
Flame retardance	Self-extinguishing conforming to UL94 (material V0)
Certificaciones de producto	UL

### Oferta sustentable

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold

### Garantía contractual

Warranty period	18 months
-----------------	-----------