

Hoja de datos del producto

Características

RUZC3M

Base rele rum universal RXM" - RUMC3 10A - 250V



Principal

Gama de producto	Zelio Relay
Tipo de producto o componente	Socket
Contact terminal arrangement	Mixed
Product compatibility	Plug-in relay RUM (3 C/O) Plug-in relay RE48A (2 C/O)
Shape of pin	Cylindrical
Device short name	RUZ
Se vende en cantidades indivisibles	10

Complementos

[Ith] conventional free air thermal current	10 A
[Ue] tensión de funcionamiento nominal	< 250 V
Tightening torque	<= 1 N.m (M3.5 screw(s))
Fixing mode	By screw mounting on panel Clip-on mounting on 35 mm symmetrical DIN rail
Marca	CE
Anchura	38 mm
Peso del producto	0.054 kg

Ambiente

Conexiones - terminales	Connector, flexible cable with cable end 1 x 0.25...1 x 2.5 mm ² / AWG 22...AWG 14
	Connector, flexible cable with cable end 2 x 0.25...2 x 1 mm ² / AWG 22...AWG 17
	Connector, solid cable without cable end 1 x 0.5...1 x 2.5 mm ² / AWG 20...AWG 14
	Connector, solid cable without cable end 2 x 0.5...2 x 1.5 mm ² / AWG 20...AWG 16
Normas	IEC 61984
Certificaciones de producto	UL CSA
Temperatura ambiente de almacenamiento	-40...85 °C
Temperatura ambiente de trabajo	-40...55 °C
IP degree of protection	IP20 conforming to EN/IEC 60529
Tensión dieléctrica	2500 V

Garantía contractual

Warranty period	18 months
-----------------	-----------