



Principal

Gama de producto	Zelio Relay
Tipo de producto o componente	Socket
Contact terminal arrangement	Separate
Product compatibility	Plug-in relay RSB (1 C/O) Plug-in relay RSB (2 C/O)
Shape of pin	Flat
Device short name	RSZ
Se vende en cantidades indivisibles	10

Complementos

[Ith] conventional free air thermal current	10 A
[Ue] tensión de funcionamiento nominal	< 250 V AC
Tightening torque	<= 0.8 N.m (M3 screw(s))
Fixing mode	By screw mounting on panel Clip-on mounting on 35 mm symmetrical DIN rail
Marca	CE
Anchura	15.5 mm
Peso del producto	0.05 kg

Ambiente

Conexiones - terminales	Screw connectors, flexible cable with cable end 1 x 0.25...1 x 2.5 mm ² / AWG 22...AWG 14 Screw connectors, flexible cable with cable end 2 x 0.25...2 x 1 mm ² / AWG 22...AWG 17 Screw connectors, solid cable without cable end 1 x 0.5...1 x 2.5 mm ² / AWG 20...AWG 14 Screw connectors, solid cable without cable end 2 x 0.5...2 x 1.5 mm ² / AWG 20...AWG 16
Normas	IEC 61984
Certificaciones de producto	UL CSA
Temperatura ambiente de almacenamiento	-40...85 °C
Temperatura ambiente de trabajo	-25...85 °C
IP degree of protection	IP20 conforming to EN/IEC 60529
Tensión dieléctrica	2500 V

Garantía contractual

Warranty period	18 months
-----------------	-----------