

Hoja de datos del producto

Características

LGY410028

Repartidores a Riel DIN 4P 100A 28 conexiones



Principal

Gama	Lineryg
Product name	Lineryg DS
Tipo de producto o componente	Distribution block

Complementos

Mounting support	DIN rail
Compatibilidad de la gama	Prisma - G Prisma - P Pragma Compact Prisma - PH Prisma - Pack Spacial Kaedra TeSys
Compatibilidad del producto	Spacial enclosures
Poles description	4P
Distribution block outgoers	4 x 7 holes
[Ue] tensión de funcionamiento nominal	230 V AC (Ph/N) 440 V AC (Ph/Ph)
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] intensidad de funcionamiento nominal	100 Aat 40 °C
[Icw] rated short-time withstand current	3 kA 1 s
[Ipk] rated peak withstand current	24 kA
Conexiones - terminales	Supply: screw terminal, 2 x 2.5...25 mm ² (rigid) Supply: screw terminal, 2 x 1.5...16 mm ² (flexible) with cable end Distribution: screw terminal, 5 x 1.5...10 mm ² (flexible) with cable end Distribution: screw terminal, 5 x 1.5...16 mm ² (rigid)
Tightening torque	Supply: Ø7.5 mm, 2 N.m with flat screwdriver Supply: Ø7.5 mm, 2 N.m with PZ2 screwdriver Distribution: Ø5.5 mm, 2 N.m with flat screwdriver Distribution: Ø5.5 mm, 2 N.m with PZ2 screwdriver
9 mm pitches	8
Altura	100 mm
Anchura	71 mm
Profundidad	50.5 mm
Peso del producto	0.21 kg
Colour	White RAL 9003

Ambiente

Pollution degree	3
Overvoltage category	III
Tensión dieléctrica	2500 V
Normas	EN/IEC 60947-7-1 EN/IEC 61439-1
Temperatura ambiente de trabajo	-25...55 °C

Oferta sustentable

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------

Garantía contractual

Warranty period	18 months
-----------------	-----------