

PRODUCT-DETAILS

UPS PowerValue 11T G2 1 kVA S

UPS PowerValue 11 T G2 1 kVA S



Información General

Extended Product Type	UPS PowerValue 11T G2 1 kVA S
Product ID	4NWP100160R0002
EAN	7640169261893
Catalog Description	UPS PowerValue 11 T G2 1 kVA S
Long Description	VFI online double conversion;900W;0min(long backup);RS232;USB;mini COM slot

Información adicional

Apparent Power Output	1000 V-A
Battery Chemical Composition	Lead-Acid
Battery Type	Portable
Battery Weight	2.5 kg
CN8	85044000
Communication Interface	USB, RS-232
Communication Protocol and Connection	SNMP
Connection Type	IEC C14
Country of Origin	China (CN)
Customs Tariff Number	85044000
Data Sheet, Technical Information	4NWD003883
Declaration of Conformity - CE	4NWD003869

E-Number (Sweden)	5257246
EAN	7640169261893
ETIM 6	EC000382 - UPS
ETIM 7	EC000382 - UPS
Efficiency	Overall 89.00 % Economy Mode (Eco-Mode) 97.50 %
Environmental Information	No declaration needed
Harmonic Distortion	5.00 %
Input Voltage (U _{in})	220 V 230 V 240 V
Input Voltage Type	AC
Instructions and Manuals	4NWD003883
Invoice Description	UPS PowerValue 11 T G2 1 kVA S
Minimum Order Quantity	1 piece
Number of Outputs	C13 Connection 3
Number of Phases	Primary - 1 Secondary - 1
Object Classification Code	G
Options Provided	Auto shut down function Potential free switch contact Network-management
Output Voltage (U _{out})	208 V 220 V 230 V 240 V
Package Level 1 Depth / Length	423 mm
Package Level 1 EAN	7640169261893
Package Level 1 Gross Weight	4.5 kg
Package Level 1 Height	330 mm
Package Level 1 Units	1 piece
Package Level 1 Width	240 mm
Power Factor	0.9
Product Main Type	PowerValue 11T G2
Product Name	UPS
Product Net Depth / Length	346 mm
Product Net Height	228 mm
Product Net Weight	3.8 kg
Product Net Width	102 mm
Rated Frequency (f)	Primary 50 Hz Primary 60 Hz Secondary 50 Hz Secondary 60 Hz
Rated Output Power	900 W
RoHS Date	0318
RoHS Information	4NWD003869
RoHS Status	Following EU Directive 2011/65/EU
Selling Unit of Measure	piece
Uninterruptible Power Supply Form Factor	Tower
Uninterruptible Power Supply Topology	On-Line Double Conversion
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
Number of Batteries	4

Categorías

SAI y acondicionador de energía → SAI → Sistemas monofásicos independientes → PowerValue 11 T G2 IEC 230V

