

withdrawable circuit breaker 3-pole, size 1 In=1250A to 500V, 50/60Hz AC Icu=66kA at 500V with mechanical lockout device with tripped signaling switch with tripped indicators with guide frame rated short-time current strength ICW 66kA/S, 3-pole Overcurrent release ETU35WT LSI Setting range according to FS with display Motorized/manual operating mechanism with memory with electrical and mechanical activation Motor and electr. calling for 220...240 V AC, 220...250 V DC Activation solenoid 220...250 V DC With 1st auxiliary release Shunt release "F", F1 220...240 V AC, 220...250 V DC without 2nd auxiliary release With door sealing frame with sealing cap against unauthorized switching off

Model	
product brand name	SENTRON
product designation	3WT air circuit breaker
design of the product	IEC 60947-2
design of the actuating element	Pushbutton
type of the driving mechanism	Motorized operating mechanism 220 - 240 V AC / 220 - 250 V DC, activation solenoid 220 - 240 V AC / 220 - 250 V DC
type of the driving mechanism motor drive	Yes
design of the overcurrent release	ETU35WT
General technical data	
number of poles	3
Field of application	CIRCUIT BREAKER
size of the circuit-breaker	I
mechanical service life (operating cycles) typical	10 000
electrical endurance (operating cycles) typical	6 000
utilization category	B
Diken-export Let-through current	DS_3WT8
Country code	EN
circuit-breaker Design	3WT8
reference code according to DIN 40719 extended according to IEC 204-2 according to IEC 750	Q
Voltage	
Rated operational voltage Ue max.	500 V
Rated insulation voltage Ui	1 000 V
- insulation voltage rated value - insulation voltage (Ui) at AC rated value	690 V 1 000 V
surge voltage resistance rated value	12 kV
operating voltage	
at AC at 50/60 Hz rated value	500 V
Protection class	
protection class IP	IP20
protection function of the overcurrent release	LSI
Main circuit	
operating frequency 1 rated value	50 Hz
Auxiliary circuit	
number of CO contacts for auxiliary contacts	2
number of NC contacts for auxiliary contacts	2
number of NO contacts for auxiliary contacts	2
operational current of auxiliary contacts at AC-15 at 230 V	6 A
Suitability	
suitability for use	Line / motor protection
disconnecting means	Yes
Adjustable parameters	
adjustable current response value current of the current-dependent overload release initial value	500 A

Product details		
product component		
• auxiliary switch	Yes	
• voltage trigger	Yes	
• undervoltage release	No	
product extension optional motor drive	No	
Product function		
product function		
• of thermal overload trip unit	adjustable	
• grounding protection	No	
• for neutral conductors short-circuit and overload proof	No	
• overload protection	Yes	
Short circuit		
operating short-circuit current breaking capacity (Ics)		
• at 240 V rated value	66 kA	
• at 415 V rated value	66 kA	
• at 500 V rated value	66 kA	
maximum short-circuit current breaking capacity (Icu)		
• at 240 V rated value	66 kA	
• at 400 V rated value	66 kA	
• at 415 V rated value	66 kA	
• at 440 V rated value	66 kA	
• at 480 V rated value	66 kA	
• at 500 V rated value	66 kA	
Connections		
arrangement of electrical connectors for main current circuit		Main connection horizontal on rear (IEC 947-2 standard)
type of connectable conductor cross-sections for auxiliary contacts		
• solid	1x (0.5 ... 2.5) mm2; 1x AWG 14	
• finely stranded with core end processing	2x 1.0 mm2	
type of electrical connection for main current circuit		busbar connection
Mechanical Design		
fastening method		drawer unit
mounting position		with vertical mounting surface +/-180° rotatable, with vertical mounting surface +/- 30° tiltable to the front and back
Environmental conditions		
ambient temperature during operation		
• minimum	-20 °C	
• maximum	70 °C	
ambient temperature during storage		
• minimum	-40 °C	
• maximum	80 °C	
Certificates		
reference code		
• according to EN 61346-2	Q	
• according to IEC 81346-2	Q	
General Product Approval		Declaration of Conformity



[Confirmation](#)



Test Certificates	other	Dangerous Good	Environment
-------------------	-------	----------------	-------------

[Special Test Certificate](#)

[Miscellaneous](#)

[Confirmation](#)

[Transport Information](#)

[Environmental Conformations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WT8121-5UG44-5AA2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WT8121-5UG44-5AA2>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WT8121-5UG44-5AA2

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



