

fixed-mounted circuit breaker 3-pole, size 2 In=2000A to 500V, 50/60Hz AC
Icu=66kA at 500V with mechanical lockout device with tripped signaling
switch with tripped indicators Overcurrent release ETU45WT LSIN Setting
range according to FS Basic functions with LC display with display With
manual operating mechanism with memory with mechanical calling without
1st auxiliary release without 2nd auxiliary release With door sealing frame

Model	
product brand name	SENTRON
product designation	3WT air circuit breaker
design of the product	IEC 60947-2
design of the actuating element	Pushbutton
design of the overcurrent release	ETU45WT
General technical data	
number of poles	3
Field of application	CIRCUIT BREAKER
size of the circuit-breaker	II
mechanical service life (operating cycles) typical	12 000
electrical endurance (operating cycles) typical	4 000
utilization category	B
Diken-export Let-through current	DS_3WT8
Country code	EN
circuit-breaker Design	3WT8
reference code according to DIN 40719 extended according to IEC 204-2 according to IEC 750	Q
Voltage	
Rated operational voltage Ue max.	500 V
Rated insulation voltage Ui	1 000 V
- insulation voltage rated value - insulation voltage (Ui) at AC rated value	690 V 1 000 V
surge voltage resistance rated value	12 kV
operating voltage	500 V
at AC at 50/60 Hz rated value	
Protection class	
protection class IP	IP20
Main circuit	
operating frequency 1 rated value	50 Hz
Auxiliary circuit	
number of CO contacts for auxiliary contacts	0
number of NC contacts for auxiliary contacts	2
number of NO contacts for auxiliary contacts	2
operational current of auxiliary contacts at AC-15 at 230 V	6 A
Suitability	
suitability for use	
disconnecting means	Yes
Product details	
product component	
- trip indicator - auxiliary switch	No Yes
Product function	
product function	
overload protection	Yes
Short circuit	
maximum short-circuit current breaking capacity (Icu)	
at 500 V rated value	66 kA

Connections	
type of connectable conductor cross-sections for auxiliary contacts	
• solid • finely stranded with core end processing	1x (0.5 ... 2.5) mm ² ; 1x AWG 14 2x 1.0 mm ²
Mechanical Design	
fastening method	fixed mounting
mounting position	with vertical mounting surface +/-180° rotatable, with vertical mounting surface +/- 30° tiltable to the front and back
Environmental conditions	
ambient temperature during operation	
• minimum • maximum	-20 °C 70 °C
ambient temperature during storage	
• minimum • maximum	-40 °C 80 °C
Certificates	
reference code	
• according to EN 61346-2 • according to IEC 81346-2	Q Q
General Product Approval	
Declaration of Conformity	



[Confirmation](#)



Test Certificates	other	Dangerous Good	Environment
Special Test Certificate	Miscellaneous	Confirmation	Transport Information
			Environmental Conformations

Further information
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WT8202-7AA00-0AA2 Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3WT8202-7AA00-0AA2 Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WT8202-7AA00-0AA2 CAX-Online-Generator http://www.siemens.com/cax Tender specifications http://www.siemens.com/specifications



