



Principal

Device short name	Motor mechanism module
Tipo de producto o componente	Motor mechanism
Aplicación de dispositivo	Automatic spring charging
Compatibilidad de la gama	Compact - Compact NSX Compact - Compact NSX DC PowerPact Multistandard
Compatibilidad del producto	PowerPact L-Frame
[In] rated current	400 A 630 A
[Uc] control circuit voltage	208...277 V AC 60 Hz 220...240 V AC 50/60 Hz

Complementos

Control type	Standard
Control signal type	Impulse Maintained
Mounting mode	Fixed
Response time	< 600 ms - during opening time < 80 ms - during closing time
Maximum operating frequency	4 per minute
Power consumption in VA	<= 500 VA - during closing time <= 500 VA - during opening time
Locking options description	1 to 3 padlocks Ø 5 to Ø 8 Padlocking in OFF position

Oferta sustentable

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0908 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Perfil Medioambiental
Product end of life instructions	Available Manual De Gestión Residuos

Garantía contractual

Warranty period	18 months
-----------------	-----------