



F 6W splitter 5...1220MHz 12dB (DOCSIS 3.1)

6-way splitter with F connectors, for CATV signals. It presents low through losses thanks to the miniaturization applied to the electronic components, which improves its electrical behavior. In addition, its Zamak chassis provides great shielding.

It is conceived for indoor installation, for wall, rack plate or standard DIN rail assembly.

DOCSIS 3.1 compatible.

Ref.	519606
Logical ref.	VT612FZ
EAN13	8424450288054

Other features

Supply method	Multiple packing
----------------------	------------------

Packaging info

Box	10 pcs.
------------	---------

Physical data

Net weight	130.00 g
Gross weight	139.00 g
Width	176.00 mm
Height	54.00 mm
Depth	18.00 mm
Main product weight	130.00 g

Highlights

- Assembly flexibility: it can be installed screwed to the wall, on rack plates with nuts on their connectors, or on a standard DIN rail (with adapter ref. 519901)
- Comfortable screwing of the cable, thanks to a 10° inclination angle of the F-connectors from the installation wall
- Space optimization in registers and cabinets: their inputs/outputs are always located on the same side
- Better organization of the installation: allows cabling passage through its rear part
- F-Series elements can be chained between them with the ground screw, requiring in this case a single grounding cable
- Signal level is maintained in outlets, even with long cable deployment, thanks to a better flatness response
- Great shielding (class A), made of Zamak
- F connectors with a longer threaded length, to facilitate and secure the installation on a rack plate
- Indoors installation
- Ground screw included
- No DC pass
- Outstanding reliability: robotized manufacturing using new generation micro-components
- 100% European design, quality and manufacturing

Technical specifications : Ref. 519606

Frequency range	MHz	5 ... 1220
Number of outputs		6
Through losses	dB	12
Rejection between outputs	dB	> 20
Connectors		"F" female