

T4N 320 PR221DS-LS/I In=320 4p F F

General Information

Extended Product Type:	T4N 320 PR221DS-LS/I In=320 4p F F
Product ID:	1SDA054121R1
EAN:	8015644552206
Catalog Description:	T4N 320 PR221DS-LS/I In=320 4p F F
Long Description:	C.BREAKER TMAX T4N 320 FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR221DS-LS/I R 320

Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Molded Case Circuit Breakers » Tmax T

Ordering

E-Number (Sweden):	3180310
EAN:	8015644552206
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Dimensions

Product Net Width:	140 mm
Product Net Height:	205 mm
Product Net Depth / Length:	103.5 mm
Product Net Weight:	4.5 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	248 mm
Package Level 1 Height:	240 mm
Package Level 1 Depth / Length:	285 mm
Package Level 1 Gross Weight:	3.5 kg
Package Level 1 EAN:	8015644552206

Additional Information

Electrical Durability:	6000 cycle 120 cycles per hour
Mechanical Durability:	20000 cycle 240 cycles per hour
Number of Poles:	4
Power Loss:	at Rated Operating Conditions per Pole 17.6 W
Product Main Type:	SACE Tmax T

Product Name:	Moulded Case Circuit Breaker
Product Type:	CB
Rated Current (I_n):	Main Circuit 320 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Voltage:	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 70 kA (230 V AC) 70 kA (380 V AC) 36 kA (400 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 30 kA (500 V AC) 25 kA (690 V) 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 70 kA (230 V AC) 70 kA (380 V AC) 36 kA (400 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 30 kA (500 V AC) 25 kA (690 V AC) 20 kA (250 V DC) 2 Poles in Series 36 kA (250 V DC) 2 Poles in Series 25 kA (750 V DC) 3 Poles in Series 16 kA
Rated Uninterrupted Current (I_u):	320 A
Release:	PR221DS-LS/I
Release Type:	EL
Short-Circuit Performance Level:	N
Standards:	IEC 60947
Sub-type:	T4
Suitable For:	T4
Suitable for Product Class:	Moulded Case Circuit Breakers
Terminal Connection Type:	Fixed Circuit-Breakers Front
Test Voltage Max (U_{test}):	3500 V
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information: [1SDC210004D0203](#)

Declaration of Conformity - 1SDL000165R0004

CE:

Environmental Information: 1SDL000143R0

Instructions and Manuals: 1SDH000436R0001

RoHS Information: 1SDL000200R0001

Classifications

ETIM 4: EC000228 - Power circuit-breaker for trafo/generator/installation prot.

ETIM 5: EC000228 - Power circuit-breaker for trafo/generator/installation prot.

ETIM 6: EC000228 - Power circuit-breaker for trafo/generator/installation prot.

ETIM 7: EC000228 - Power circuit-breaker for trafo/generator/installation protection

Object Classification Code: Q

UNSPSC: 39121100

WEEE Category: 5. Small Equipment (No External Dimension More Than 50 cm)



© Copyright 2020 ABB