

## PRODUCT-DETAILS

# T5S 400 PR221DS-LS/I In=400 3p F F

# T5S 400 PR221DS-LS/I In=400 3p F F



## Información General

|                       |                                                                                                               |
|-----------------------|---------------------------------------------------------------------------------------------------------------|
| Extended Product Type | T5S 400 PR221DS-LS/I In=400 3p F F                                                                            |
| Product ID            | 1SDA054333R1                                                                                                  |
| EAN                   | 8015644554316                                                                                                 |
| Catalog Description   | T5S 400 PR221DS-LS/I In=400 3p F F                                                                            |
| Long Description      | C.BREAKER TMAX T5S 400 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR221DS-LS/I R 400 |

## Clasificación

|                        |               |
|------------------------|---------------|
| E-Number (Sweden)      | 3180383       |
| EAN                    | 8015644554316 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85362090      |

## Dimensiones

|                            |          |
|----------------------------|----------|
| Product Net Width          | 140 mm   |
| Product Net Height         | 205 mm   |
| Product Net Depth / Length | 103.5 mm |
| Product Net Weight         | 4.824 kg |

## Información de Embalaje

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Width          | 248 mm        |
| Package Level 1 Height         | 240 mm        |
| Package Level 1 Depth / Length | 285 mm        |
| Package Level 1 Gross Weight   | 5.1 kg        |
| Package Level 1 EAN            | 8015644554316 |

## Información Adicional

|                                                             |                                                                                                                                                                                                                                                                                |
|-------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electrical Durability                                       | 7000 cycle<br>60 cycles per hour                                                                                                                                                                                                                                               |
| Mechanical Durability                                       | 20000 cycle<br>120 cycles per hour                                                                                                                                                                                                                                             |
| Number of Poles                                             | 3                                                                                                                                                                                                                                                                              |
| Power Loss                                                  | at Rated Operating Conditions per Pole 16.5 W                                                                                                                                                                                                                                  |
| Product Main Type                                           | SACE Tmax T                                                                                                                                                                                                                                                                    |
| Product Name                                                | Moulded Case Circuit Breaker                                                                                                                                                                                                                                                   |
| Product Type                                                | CB                                                                                                                                                                                                                                                                             |
| Rated Current ( $I_n$ )                                     | Main Circuit 400 A                                                                                                                                                                                                                                                             |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | 8 kV                                                                                                                                                                                                                                                                           |
| Rated Insulation Voltage ( $U_i$ )                          | 1000 V                                                                                                                                                                                                                                                                         |
| Rated Operational Voltage                                   | 690 V AC                                                                                                                                                                                                                                                                       |
| Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )  | (220 V AC) 85 kA<br>(230 V AC) 85 kA<br>(380 V AC) 50 kA<br>(400 V AC) 50 kA<br>(415 V AC) 50 kA<br>(440 V AC) 40 kA<br>(500 V AC) 30 kA<br>(690 V AC) 25 kA                                                                                                                   |
| Rated Short-time Withstand Current ( $I_{cw}$ )             | for 1 s 5 kA                                                                                                                                                                                                                                                                   |
| Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ) | (220 V AC) 85 kA<br>(230 V AC) 85 kA<br>(380 V AC) 50 kA<br>(400 V AC) 50 kA<br>(415 V AC) 50 kA<br>(440 V AC) 40 kA<br>(500 V AC) 30 kA<br>(690 V AC) 25 kA<br>(250 V DC) 2 Poles in Series 50 kA<br>(500 V DC) 2 Poles in Series 36 kA<br>(750 V DC) 3 Poles in Series 25 kA |
| Rated Uninterrupted Current ( $I_u$ )                       | 400 A                                                                                                                                                                                                                                                                          |
| Release Type                                                | EL                                                                                                                                                                                                                                                                             |
| Standards                                                   | IEC                                                                                                                                                                                                                                                                            |
| Sub-type                                                    | T5                                                                                                                                                                                                                                                                             |
| Suitable For                                                | T5                                                                                                                                                                                                                                                                             |
| Suitable for Product Class                                  | Moulded Case Circuit Breakers                                                                                                                                                                                                                                                  |
| Terminal Connection Type                                    | Fixed Circuit-Breakers<br>Front                                                                                                                                                                                                                                                |
| Test Voltage Max ( $U_{test}$ )                             | 3500 V                                                                                                                                                                                                                                                                         |
| Test Voltage at Industrial Frequency for 1 Minute           | 3500 V                                                                                                                                                                                                                                                                         |

Version

F

## Certificados y Declaraciones (Número de Documento)

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SDC210004D0203 |
| Declaration of Conformity - CE    | 1SDL000165R0005 |
| Environmental Information         | 1SDL000143R0    |
| GL Certificate                    | 1SDL000163R0062 |
| Instructions and Manuals          | 1SDH000437R0001 |
| Instructions and Manuals (Part 2) | ITSCE-RH0100001 |
| RoHS Information                  | 1SDL000200R0001 |

## Clasificaciones

|                            |                                                                              |
|----------------------------|------------------------------------------------------------------------------|
| ETIM 4                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 5                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 6                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 7                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q                                                                            |
| UNSPSC                     | 39121100                                                                     |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm)                   |

## Categorías

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → Tmax T

