

# Product data sheet

Specifications



## Switch, Miluz, 1 way, 10AX, 250V, golden

S3B62115

### Main

Range	Miluz
Product or component type	Switch

### Complementary

Device presentation	Complete mechanism
Device mounting	Flush
Colour tint	Brown (RAL 8014) Golden
Type of packing	Flow-pack
Switch function	Double 1-way
Ambient air temperature for operation	-5...45 °C
Number of rocker	2
Local signalling	Without pilot light
Marking	1 - L
Rated current	10 A
[Ue] rated operational voltage	250 V AC
Material	Thermoplastic ABS-UV stabilised: rocker PA66: casing PS (polystyrene): fixing frame Thermoplastic ABS-UV stabilised: cover frame
Number of modules	2 modules
Fixing mode	By screws
Connections - terminals	Screw-clamp terminals
Number of cables	2
Cable cross section	4 mm²
Wire stripping length	12 mm
Surface finish	Glossy Matt
AWG gauge	AWG 12
Height	115.0 mm
Width	77.0 mm

Depth	40.0 mm
Embedding depth	26 mm
Projecting depth	14.5 mm

## Environment

Standards	ABNT NBR NM 60669-2-1 NMX J-508 ANCE IEC 60669
IP degree of protection	IP2x

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	75.1 g
Package 1 Height	4.0 cm
Package 1 width	9.5 cm
Package 1 Length	19.0 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Weight	1.502 kg
Package 2 Height	21.5 cm
Package 2 width	15.8 cm
Package 2 Length	26.5 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>