

X1N1600PR332 / PLSIGIn = 1600A3pFF

Información general

Tipo de producto extendido:	X1N1600PR332 / PLSIGIn = 1600A3pFF
ID del Producto:	1SDA062610R1
EAN:	8015644651565
Descripción del catálogo:	X1N 1600 PR332 / P L SIG Entrada = 1600A 3p FF
Descripción larga:	C. INTERRUPTOR EMAX X1N 1600 FIJO DE TRES POLOS CON TERMINALES FRONTALES Y LIBERACIÓN DE ESTADO SÓLIDO EN AC PR332 / P-LSIG R 1600 EQUIPADO CON: 4 CONTACTOS AUXILIARES Y C. INTERRUPTOR EN POSICIÓN ABIERTO-CERRADO

Categorías

Productos »Productos y sistemas de baja tensión» Disyuntores »Disyuntores de potencia» Emax

Ordenando

EAN:	8015644651565
Cantidad mínima de pedido:	1 pieza
Número de arancel aduanero:	85362090

Dimensiones

Ancho neto del producto:	210 mm
Altura neta del producto:	268 milímetros
Profundidad / longitud neta del producto:	181 mm
Product Net Weight:	11 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	280 mm
Package Level 1 Height:	350 mm
Package Level 1 Depth / Length:	360 mm
Package Level 1 Gross Weight:	12.5 kg
Package Level 1 EAN:	8015644609139

Additional Information

Current Type:	AC
Electrical Durability:	Ue =< 440 V 3000 cycle Ue = 500 ... 690 V 1000 cycle 30 cycles per hour
Mechanical Durability:	12500 cycle 60 cycles per hour
Number of Poles:	3
Power Loss:	203 W
Product Main Type:	SACE Emax
Product Name:	Air Circuit Breaker
Product Type:	Air Circuit Breaker
Rated Current (I_n):	1600 A
Rated Voltage (U_g):	690 V

Rated Impulse Withstand Voltage (U_{imp}):	12 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Current (I_e):	1600 A
Rated Operational Voltage:	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 50 kA (230 V AC) 50 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 42 kA (660 V AC) 42 kA (690 V AC) 42 kA
Rated Short-time Withstand Current (I_{cw}):	for 1 s 42 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 65 kA (230 V AC) 65 kA (380 V AC) 65 kA (400 V AC) 65 kA (415 V AC) 65 kA (440 V AC) 65 kA (500 V AC) 50 kA (660 V AC) 50 kA (690 V AC) 50 kA
Rated Uninterrupted Current (I_u):	1600 A
Release:	PR332/P L SIG
Release Type:	EL
Short-Circuit Performance Level:	N
Standards:	IEC
Sub-type:	X1
Terminal Connection Type:	Fixed Circuit-Breakers Front
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	<u>1SDC200009D0203</u>
Declaration of Conformity - CE:	<u>1SDL000165R0018</u>
Environmental Information:	<u>1SDC200009D0201</u>
Instructions and Manuals:	<u>1SDH000606R0004</u> <u>1SDH000587R0002</u>
RoHS Information:	<u>1SDL000203R0001</u>

Classifications

ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6:	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
Object Classification Code:	Q

UNSPSC:

39120000

WEEE Category:

5. Small Equipment (No External Dimension More Than 50 cm)



© Copyright 2021 ABB