

PRODUCT-DETAILS

A1B 125 TMF 15-400 3p F F

A1B 125 TMF 15-400 3p F F



Información General

Extended Product Type	A1B 125 TMF 15-400 3p F F
Product ID	1SDA066697R1
EAN	8015644006075
Catalog Description	A1B 125 TMF 15-400 3p F F
Long Description	C.BREAKER FORMULA A1B 125 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 15-400 A

Clasificación

EAN	8015644006075
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensiones

Product Net Width	76.2 mm
Product Net Height	130 mm
Product Net Depth / Length	60 mm
Product Net Weight	0.8 kg

Información de Embalaje

Package Level 1 Units	1 piece
Package Level 1 Width	136.5 mm
Package Level 1 Height	124 mm
Package Level 1 Depth / Length	110.5 mm
Package Level 1 Gross Weight	0.8 kg
Package Level 1 EAN	8015644006075

Información Adicional

Electrical Durability	1500 cycle
Mechanical Durability	Nr. Operations 8500 cycle
Number of Poles	3
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Power Loss	at Rated Operating Conditions per Pole 2.5 W
Product Main Type	SACE FORMULA
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	Main Circuit 15 A
Rated Impulse Withstand Voltage (U_{imp})	6 kV
Rated Insulation Voltage (U_i)	690 V
Rated Operational Voltage	550 V AC 250 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 12.5 kA (380 V AC) 9 kA (415 V AC) 5 kA (440 V AC) 5 kA (480 V AC) 5 kA (500 V AC) 2.5 kA (250 V DC) 2 Poles in Series 2.5 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(240 V AC) 25 kA (380 V AC) 18 kA (415 V AC) 18 kA (440 V AC) 15 kA (480 V AC) 10 kA (500 V AC) 5 kA (250 V DC) 5 kA
Rated Uninterrupted Current (I_u)	125 A
Release Type	TM
Standards	IEC
Sub-type	A1
Terminal Connection Type	Front
Version	F

Certificados y Declaraciones (Número de Documento)

Data Sheet, Technical Information	1SDC210032D0204
Declaration of Conformity - CE	9AKK106713A5519
Environmental Information	1SDL000183R0001
Instructions and Manuals	1SDH000717R0001

Clasificaciones	
ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categorías

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → FORMULA

