

PRODUCT-DETAILS

6817/32-24

6817/32-24 Busch-Presence detector Universal, e-contact 12 meters



Información General

Extended Product Type	6817/32-24
Product ID	2CKA006800A2738
EAN	4011395217597
Catalog Description	6817/32-24 Busch-Presence detector Universal, e-contact 12 meters
Long Description	Master presence detector with mixed light measurement. For switching lighting systems that depend on brightness and movement. With electronic switch contact for LED operation. Detection range (for installation height of 3 m): circular Seated persons: up to Ø 10 m, walking persons: up to Ø 12 m. Extension of the detection range by means of master/slave combination. Visible height 23 mm. For semiautomatic and fully automatic operation. Additional activation/deactivation possibility through pushbutton input. With continuous light/continuous off function (8 hours), activation via intelligent extension unit input possible. With brightness-independent test mode for evaluating the detection zone. With teach-in function of the brightness switching threshold, IR service remote control required. With detection display in test mode. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Adjustment elements accessible on the front side. Surveillance density: 72 sectors with 640 switching segments. Switch-off delay: approx. 1 min. - 30 min. or short-time pulse adjustable. Remote control possible via IR service remote control 6843. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm.

Clasificación

EAN	4011395217597
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Dimensiones

Product Net Width	0.094 m
Product Net Height	0.094 m
Product Net Depth / Length	0.059 m
Product Net Weight	255 g

Información de Embalaje

Package Level 1 Units	1 piece
Package Level 1 Width	0.141 m
Package Level 1 Height	0.095 m
Package Level 1 Depth / Length	0.165 m
Package Level 1 Gross Weight	255 g
Package Level 1 EAN	4011395217597

Ambiente

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Información Adicional

Auxiliary Voltage AC/DC	110 V AC/DC 230 V AC/DC
Brand / Label	Busch-Jaeger
Color	studio white matt
Degree of Protection	IP40
Frequency (f)	50...60 Hz
Illuminance	5...2000 lx
Material	Material quality: Thermoplastic Material: Plastic
Mounting Type	Flush-mounted
Number of Outputs	1
Product Main Type	Busch-Presence detector Universal, e-contact
Product Name	Busch-Presence detector Universal, e-contact 12 meters
Product Range	Movement detector
Rated Voltage (U _r)	230 V
RoHS Date	20150724
Surface Finishing	Surface protection: Untreated Surface finishing: Matt

Certificados y Declaraciones (Número de Documento)

Data Sheet, Technical Information	2CKA0001373B9426
Declaration of Conformity - CE	2CKA100000E0693
Instructions and Manuals	2CKA000173B9213
RoHS Information	9AKK104295D8727

Clasificaciones

ETIM 5

EC000133 - Movement sensor complete

ETIM 6	EC000133 - Movement sensor complete
ETIM 7	EC000133 - Movement sensor complete
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categorias

Productos y sistemas de baja tensión → StandAlone Electronics → Presence Detector → Presence Detector Series → IR Controlled Devices (Master) → Presence Detector Universal, e Contact

