

## PRODUCT-DETAILS

# XT1D 160 3p F F

# XT1D 160 3p F F



### Información General

|                       |                                                                         |
|-----------------------|-------------------------------------------------------------------------|
| Extended Product Type | XT1D 160 3p F F                                                         |
| Product ID            | 1SDA068208R1                                                            |
| EAN                   | 8015644021047                                                           |
| Catalog Description   | XT1D 160 3p F F                                                         |
| Long Description      | SWITCH-DISCONNECTOR TMAX XT1D 160 FIXED THREE-POLE WITH FRONT TERMINALS |

### Clasificación

|                        |               |
|------------------------|---------------|
| EAN                    | 8015644021047 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85362090      |

### Dimensiones

|                            |          |
|----------------------------|----------|
| Product Net Width          | 76.2 mm  |
| Product Net Height         | 130 mm   |
| Product Net Depth / Length | 70 mm    |
| Product Net Weight         | 1.028 kg |

### Información de Embalaje

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Width          | 128 mm        |
| Package Level 1 Height         | 135 mm        |
| Package Level 1 Depth / Length | 143 mm        |
| Package Level 1 Gross Weight   | 1.082 kg      |
| Package Level 1 EAN            | 8015644021047 |

## Información Adicional

|                                                       |                                                                  |
|-------------------------------------------------------|------------------------------------------------------------------|
| Electrical Durability                                 | 120 cycles per hour<br>8000 cycle                                |
| Mechanical Durability                                 | Nr. Operations 240 cycles per hour<br>Nr. Operations 25000 cycle |
| Number of Poles                                       | 3                                                                |
| Opening Time                                          | CB with SOR 15 ms<br>CB with UVR 15 ms                           |
| Order Multiple                                        | 1 piece                                                          |
| Product Main Type                                     | SACE Tmax XT                                                     |
| Product Name                                          | Lasttrennschalter                                                |
| Product Type                                          | SD                                                               |
| Rated Frequency (f)                                   | 50 / 60 Hz                                                       |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> )   | 8 kV                                                             |
| Rated Insulation Voltage (U <sub>i</sub> )            | 800 V                                                            |
| Rated Operational Voltage                             | 690 V AC<br>500 V DC                                             |
| Rated Short-time Withstand Current (I <sub>cw</sub> ) | for 1 s 2 kA                                                     |
| Rated Uninterrupted Current (I <sub>u</sub> )         | 160 A                                                            |
| Standards                                             | IEC                                                              |
| Sub-type                                              | XT1                                                              |
| Terminal Connection Type                              | Fixed Circuit-Breakers                                           |
| Version                                               | F                                                                |

## Certificados y Declaraciones (Número de Documento)

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SDC210100D0204<br>1SDC210099D0204 |
| Declaration of Conformity - CE    | 9AKK106713A5532                    |
| Environmental Information         | 1SDL000190R0001                    |
| Instructions and Manuals          | 1SDH000719R0001                    |

## Clasificaciones

|                            |                                                                         |
|----------------------------|-------------------------------------------------------------------------|
| ETIM 4                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 5                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 6                     | EC000216 - Switch disconnector                                          |
| ETIM 7                     | EC000216 - Switch disconnector                                          |
| Object Classification Code | Q                                                                       |
| UNSPSC                     | 39120000                                                                |

---

## Categorías

---

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → Tmax XT

