

Product data sheet

Specifications



Italian socket outlet, Miluz, 2P+E, 10A/16A, 250V, bipasso, 1 module, graphite

S3B70236

Main

Range	Miluz
Product or component type	Socket-outlet
Fixing mode	Clip-in

Complementary

Device presentation	Mechanism
Outlet standard description	With earthing contact
Outlet poles configuration	2P + E
Device mounting	Flush
Colour tint	Graphite (RAL 7016)
Outlet standard	Italian
Type of packing	Flow-pack
[In] rated current	10.0 A
[Ue] rated operational voltage	250 V AC
Material	ASA + PC: centre plate PC (polycarbonate): casing
Surface finish	Glossy
Number of modules	1 module
Connections - terminals	Screw-clamp terminals
Number of cables	2
Cable cross section	1.5...4 mm²
Wire stripping length	11 mm
AWG gauge	AWG 12
Height	22.0 mm
Width	40.0 mm
Depth	44.0 mm
Embedding depth	26.0 mm
Projecting depth	8.5 mm

Environment

Standards	NCh 2027/1 NCh 2027/2
IP degree of protection	IP2x

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	23.0 g
Package 1 Height	2.2 cm
Package 1 width	8.5 cm
Package 1 Length	14.0 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	50
Package 2 Weight	1.15 kg
Package 2 Height	21.5 cm
Package 2 width	15.8 cm
Package 2 Length	26.5 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)