

E2.2N 2000 Ekip Dip LI 3p F HR

Información general

Tipo de producto extendido: E2.2N 2000 Ekip Dip LI 3p F HR

Identificación de producto: 1SDA071031R1

EAN: 8015644748814

Descripción del catálogo: E2.2N 2000 Ekip Dip LI 3p F HR

Descripción larga: C. INTERRUPTOR SACE EMAX2 E2.2N 2000 FIJO DE TRES POLOS CON TERMINALES TRASERO HORIZONTAL Y ESTADO SÓLIDO LIBERACIÓN EN AC EKIP / DIP-LI R 2000 EQUIPADO CON: 4 CONTACTOS AUXILIARES Y C. INTERRUPTOR EN POSICIÓN ABIERTO-CERRADO

Categorías

Productos »Productos y sistemas de baja tensión» Disyuntores »Disyuntores de potencia» Emax 2

Ordenando

EAN: 8015644748814

Cantidad mínima de pedido: 1 pieza

Número de arancel aduanero: 85362090

Dimensiones

Ancho neto del producto: 276 milímetros

Altura neta del producto: 371 milímetros

Profundidad / longitud neta del producto: 270 mm

Product Net Weight: 41 kg

Container Information

Package Level 1 Units: 1 piece

Package Level 1 Width: 515 mm

Package Level 1 Height: 610 mm

Package Level 1 Depth / Length: 515 mm

Package Level 1 Gross Weight: 46 kg

Package Level 1 EAN: 8015644748814

Environmental

RoHS Status: Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Additional Information

Current Type:	AC
Electrical Durability:	Ue =< 440 V 10000 cycle Ue = 500 ... 690 V 8000 cycle 30 cycles per hour
Mechanical Durability:	25000 cycle 60 cycles per hour
Number of Poles:	3
Power Loss:	212 W
Product Main Type:	SACE Emax 2
Product Name:	Air Circuit Breaker
Product Type:	Air Circuit Breaker
Rated Service Short-Circuit Breaking Capacity, in % of I_{cu} (I_{cs}):	100 %
Rated Current (I_n):	2000 A
Rated Voltage (U_r):	690 V
Rated Impulse Withstand Voltage (U_{imp}):	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U_i):	AC 1000 V
Rated Operational Voltage:	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 66 kA (230 V AC) 66 kA (380 V AC) 66 kA (400 V AC) 66 kA (415 V AC) 66 kA (440 V AC) 66 kA (500 V AC) 66 kA (660 V AC) 66 kA (690 V AC) 66 kA
Rated Short-time Withstand Current (I_{cw}):	for 1 s 66 kA for 3 s 50 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(400 V AC) 66 kA (415 V AC) 66 kA (440 V AC) 66 kA (500 V AC) 66 kA (525 V AC) 66 kA (690 V AC) 66 kA
Rated Uninterrupted Current (I_u):	2000 A
Release:	Ekip Dip LI
Release Type:	EL
Short-Circuit Performance Level:	N

Standards:	IEC
Sub-type:	E2.2
Terminal Connection Type:	Rear flat Horizontal
Version:	F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information: 1SDC200023D0209

Declaration of Conformity - CE: 9AKK106713A5902

Environmental Information: Not Available

Instructions and Manuals: 1SDH001000R0002

Classifications

ETIM 4: EC000228 - Power circuit-breaker for trafo/generator/installation prot.

ETIM 5: EC000228 - Power circuit-breaker for trafo/generator/installation prot.

ETIM 6: EC000228 - Power circuit-breaker for trafo/generator/installation prot.

ETIM 7: EC000228 - Power circuit-breaker for trafo/generator/installation protection

Object Classification Code: Q

WEEE Category: 5. Small Equipment (No External Dimension More Than 50 cm)



© Copyright 2021 ABB