Technical Datasheet Cable Ladder System



GRP-Elbow 2 x 45°

pultruded, with unperforated side rail centre pieces, with connector tabs for connection as well as in the centre piece with upward open unperforated rung made of C-profile with approx. 15 mm slot width.

ULBA 100.150

EAN Code: 4013339959013 Smallest packaging unit:1 pc.












the photorealistic images are to be considered as reference images







Article Description

GRP-elbow for UL, adjustable, 100x150 mm, with integrated connector, glass fiber reinforced polyester, pultruded, RAL 7032, pebble grey

Additional Price Information

Article group	N15
quantity unit	pcs.

Weight

Weight per quantity unit	2,200 kg/pcs.
Weight in kg per 100	220 kg/100pcs.

Aktualisiert am 24/6/2025 Page 1/2

Technical Datasheet Cable Ladder System

ULBA 100.150

the photorealistic images are to be considered as reference images

Physical Article Dimensions

Height	100.00 mm
Width	148.00 mm
Depth/length	500 mm

Packing Dimension

1 piece = 1 piec	9	√ VP1-smallest	packaging unit (F	PU)	
Lenght	500 mm	Width	148.00 mm	Height	100.00 mm
Gross weight	2,2 kg	Volume	$0,007 \text{ m}^3$		
Min. quantity	1.00 pcs.	Max. Quantity	1.00 pcs.		

Tender Text

GRP elbow 2 x 45° , pultruded, with unperforated side rail centre pieces, with connector lugs for connection as well as in the centre piece with upwardly open unperforated rung made of C-profile with approx. 15 mm slot width, for producing 2 x 45° vertically falling cable ladder run, please order proportionate fixing accessories separately, halogen-free.

Please pay attention to the following during assembly:

- The fitting must be supported with outriggers at each cable ladder access point.
- To ensure proper installation, the connectors must be bolted with 4 FKM 6×20 E4 at each cable ladder access.

GRP elbow $2 \times 45^{\circ}$ with stainless steel connecting lugs (1) on request.

Used for: GRP cable ladder UL 100...

GRP cable ladder ULL 100...

Dimensions (approx. dimensions)

H x W : 100 x 150 mm

Outside dimensions : 372 mm

Radius R : 400 mm

Material: UP-GF (glass fibre reinforced polyester)

Material screws : stainless steel, material no. 1.4404, AISI 316L

Colour : pebble grey
RAL : 7032 (similar)

NIEDAX Model No. : ULBA 100.150
EP Material EP Wage

Unit price/piece

Safety & Environment

REACH Date	21.01.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	FR
Customs tarif number	39259020

Aktualisiert am 24/6/2025 Page 2 / 2